



	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
	PRODUCT DESCRIPTION			
Surface treatment	-	-	-	Protocolsol <small>TRIPLE ACTION</small>
Surface complex	-	-	-	
Foam	-	-	-	
Thickness	EN 428	-	mm	2
Weight	EN 430	-	kg/m ²	2.58
Length	EN 426	-	lm	20
Width	EN 426	-	lm	2
	SPORT PROPERTIES			
Shock absorption	EN 14808	≥ 25	%	-
Vertical deformation	EN 14809	≤ 3.5	mm	-
Energy return	NF P 90 203	≥ 0.31	m/s	-
Sliding coefficient	EN 13036-4	80 to 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	≥ 90
Ball speed	UEFA	50 to 65	cm	-
	ITF	-	-	-
	TECHNICAL CHARACTERISTICS			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥ 8
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
	CLASSIFICATION			
Fire	EN 13501-1	-	-	
Anti-bacterial activity (E. coli - S. aureus - MRSA) (3)	ISO 22196	-	-	> 99 % inhibits growth
	DECLARATION OF PERFORMANCE			
	DOP n°xxx	-	-	Fire Sliding Coefficient Abrasion Resistance Resistance to rolling load

(3) The implementation of an effective cleaning method is the best defence against infection

